

<b>Model Name</b>	<b>KMU-100</b>
<b>Product Name</b>	<b>4K Multicamera Processor</b>
<b>Video Input</b>	<p>2 sets of SDI Input: each set of 4x SDI 1x 3Gb/s or 12Gb/s SD/HD/4K. Supports single link 4:2:2 3x 3Gb/s SD/HD/4K. Supports single link, dual link, and quad link 4:2:2</p> <p>2x HDMI Input: each of HDMI support for Ultra HD 4K 60p in 4:2:0/4:2:2</p>
<b>Supported Video Input Resolution</b>	<p>3840x2160p 23.98/24/25/29.97/30/50/59.94/60. 1080p 23.98/24/25/29.97/30 1080i 50/59.94/60 1080PsF 23.98/24/25/29.97/30 720p 50/59.94/60</p>
<b>Video Output</b>	<p>2 sets of SDI output: each set of 4x SDI 1x 3Gb/s or 12Gb/s SD/HD/4K. Supports single link 4:2:2 3x 3Gb/s SD/HD/4K. Supports single link, dual link, and quad link 4:2:2</p>
<b>Support Video Output Resolution</b>	<p>1080p 25/29.97/30/50/59.94/60 1080i 50/59.94/60 720p 50/59.94/60 625/50i PAL, 525/59.94i NTSC</p>
<b>Multiview Out</b>	HDMI 1.4 x2
<b>Multiview Mode</b>	Preview, Motion, Quad
<b>Audio Input</b>	<p>SDI: 16 Ch embedded in HD/4K. 8 Ch embedded in SD HDMI: 8 Ch embedded in SD, HD and Ultra HD 4K</p>
<b>Audio Output</b>	<p>SDI: 16 Ch embedded in HD/4K. 8 Ch embedded in SD. HDMI: 8 Ch embedded in SD, HD and Ultra HD 4K</p>
<b>Audio Sampling</b>	Television standard sample rate of 48 kHz at 24-bit
<b>Reference Input</b>	Blackburst, Tri-level
<b>Control Interface</b>	<p>Ethernet RJ45 for control, configuration and updates RS-232 x1 input for controlling configuration</p>

	RS-422 x1 input with external keyboard support GPIO x1
<b>Power Supply</b>	DC 12V 5A
<b>MSRP</b>	USD 4,995