

<b>Model Name</b>	<b>PTC-150T</b>
<b>Product Name</b>	<b>HD/SD-SDI PTZ Camera</b>
<b>Video Format</b>	1080p 59.94/50/29.97/25 1080i 59.94/50 720p 59.94/50 480i, 576i (on CVBS)
<b>Image Sensor</b>	1/2.8" CMOS
<b>Effective Pixels</b>	2.14 Mega pixels
<b>S/N Ratio</b>	50dB
<b>Min. Illumination</b>	Color: 0.4 lx B/W: 0.03 lx (F1.6, 1/30 sec, 50IRE, Gain: High)
<b>Electronic Shutter</b>	1/25 (1/30), 1/50 (1/60), 1/75(1/90), 1/100, 1/120 (1/125), 1/150(1/180), 1/215( 1/250), 1/300(1/350), 1/425(1/500), 1/600(1/725), 1/1000, 1/1250(1/1500)
<b>Zoom Ratio</b>	30x Optical Zoom
<b>Gamma Control</b>	Off / Normal / Standard Mode 1-4
<b>Iris Control</b>	Auto / Manual
<b>Digital Noise Reductions</b>	Yes
<b>Language</b>	English
<b>White Balance</b>	3200K/ Tungsten, 4200K/ Fluorescent, 5600K/ Outdoor, Manual, One-Push, Auto
<b>AGC / Gain Control</b>	Auto / Manual Max. Gain Limit
<b>Mirror / Flip Image</b>	Yes
<b>Focus Mode</b>	Auto / Manual
<b>Panning/Tilting Range</b>	Pan: 270°, Tilt: +90° to -20°
<b>Panning/Tilting Speed</b>	Manual: 1~150°/Sec Swing: 1~150°/Sec
<b>Preset</b>	50 Position
<b>Focal Length/ Aperture</b>	f=4.3 mm (WIDE) to 129 mm (TELE) F1.6 to F4.7
<b>Angle of View</b>	Approx. 63.7° (WIDE END) / 2.3° (TELE END)
<b>Image Compensation</b>	Day & Night Function

<b>Video Output</b>	HDBaseT x 1 3G-SDI x1 HDMI x1 CVBS x1
<b>Tally LED</b>	Dual Color (Red, Green)
<b>Filter</b>	M52.0 x 0.75mm Thread with UV Protection
<b>RoHS</b>	Compliant
<b>Protocol</b>	VISCA, DVIP
<b>Remote Control</b>	RS-422: Transmit up to 1000m HDBaseT (RJ45): Transmit up to 100m
<b>F/W Update</b>	USB
<b>IR Control</b>	Yes
<b>Camera Control Unit</b>	HS-1500T, HS-1600T, RMC-300C
<b>Power</b>	DC 12V 29W
<b>Tripod Mount</b>	1/4-20 UNC
<b>Option</b>	WM-1
<b>Color</b>	Dark Blue
<b>Dimension</b>	173(L) x 189(W) x 219(H) mm
<b>Weight</b>	2.7Kg
<b>Operating Temp.</b>	0~50 °C